



## PERFORMANCE CURVE

### MAGNET DRIVE CENTRIFUGAL PUMP

Item No.: \_\_\_\_\_  
 Job No.: \_\_\_\_\_  
 \_\_\_\_\_

● **Pump Model** MP220-100-6\*007\*K26\*-2  
 Magnet Coupling Type:         K20x6N          
 Eddy Current Loss:         0.14         kW

● **Pump Specification**  
 Total Head:         10         m  
 Capacity:         4.44         m<sup>3</sup>/hr            74         L/min  
 Speed:         2930         min<sup>-1</sup>  
 Min.Flow:         0.6         m<sup>3</sup>/hr            10         L/min  
 NPSH av/req:         / -         m

● **Liquid**  
 Name:         -          
 Specific Gravity:         1          
 Viscosity:         1         mPa·s

● **Motor**  
 Power:         0.75 / 1.1         kW

Remark: Recommended Selection Range; 10~75L/min  
 For low Specific Gravity liquid such as Hydrocarbon,  
 please consult with the manufacturer.

Work No.	Standard	Dwg No.	MP220-100-K26-52-0
APP'D	CH'D	DWN.	
<i>A. Miyahara</i>	M.Murakami	M.Murakami	

**SANWA HYDROTECH CORP.**

承
品
計