



## PERFORMANCE CURVE

### MAGNET DRIVE CENTRIFUGAL PUMP

Item No.: \_\_\_\_\_

Job No.: \_\_\_\_\_

: \_\_\_\_\_

● **Pump Model** MP220-110-6\*015\*K20\*-2  
 Magnet Coupling Type:           K20N            
 Eddy Current Loss:           0.19           kW

● **Pump Specification**  
 Total Head:           12           m  
 Capacity:           5.04           m<sup>3</sup>/hr              84           L/min  
 Speed:           2930           min<sup>-1</sup>  
 Min.Flow:           0.6           m<sup>3</sup>/hr              10           L/min  
 NPSH av/req:           / -           m

● **Liquid**  
 Name:           -            
 Specific Gravity:           1            
 Viscosity:           1           mPa·s

● **Motor**  
 Power:           1.5           kW

Remark: Recommended Selection Range; 10~85L/min  
 For low Specific Gravity liquid such as Hydrocarbon,  
 please consult with the manufacturer.

Work No. | **Standard** | Dwg No. | **MP220-110-K20-52-0**

|                             |                     |                     |
|-----------------------------|---------------------|---------------------|
| APP'D<br><i>A. Miyahara</i> | CH'D<br>M. Murakami | DWN.<br>M. Murakami |
|-----------------------------|---------------------|---------------------|

**SANWA HYDROTECH CORP.**

|   |
|---|
| 承 |
| 品 |
| 計 |