



## PERFORMANCE CURVE

### MAGNET DRIVE CENTRIFUGAL PUMP

Item No.: \_\_\_\_\_

Job No.: \_\_\_\_\_

● **Pump Model** MP220-110-6\*007\*K26\*-2  
 Magnet Coupling Type:         K20x6N          
 Eddy Current Loss:     0.14     kW

● **Pump Specification**  
 Total Head:     12     m  
 Capacity:     4.92     m<sup>3</sup>/hr        82     L/min  
 Speed:     2930     min<sup>-1</sup>  
 Min.Flow:     0.6     m<sup>3</sup>/hr        10     L/min  
 NPSH av/req:     / -     m

● **Liquid**  
 Name:         -          
 Specific Gravity:     1      
 Viscosity:     1     mPa·s

● **Motor**  
 Power:     0.75 / 1.1     kW

Remark: Recommended Selection Range; 10~80L/min  
 For low Specific Gravity liquid such as Hydrocarbon,  
 please consult with the manufacturer.

Work No. | **Standard** | Dwg No. | **MP220-110-K26-52-0**

APP'D <i>A. Miyahara</i>	CH'D M. Murakami	DWN. M. Murakami
-----------------------------	---------------------	---------------------



SANWA HYDROTECH CORP.

承
品
計