



## PERFORMANCE CURVE

### MAGNET DRIVE CENTRIFUGAL PUMP

Item No.: \_\_\_\_\_

Job No.: \_\_\_\_\_

: \_\_\_\_\_

- **Pump Model** MP222-140-6\*022\*K32\*-2  
 Magnet Coupling Type:           K32N            
 Eddy Current Loss:           0.34           kW

- **Pump Specification**  
 Total Head:           21           m  
 Capacity:           6.6           m<sup>3</sup>/hr              110           L/min  
 Speed:           2940           min<sup>-1</sup>  
 Min.Flow:           0.6           m<sup>3</sup>/hr              10           L/min  
 NPSH av/req:           / -           m

- **Liquid**  
 Name:           -            
 Specific Gravity:           1            
 Viscosity:           1           mPa·s

- **Motor**  
 Power:           2.2 / 4.0           kW

Remark: Recommended Selection Range; 10~110L/min  
 For low Specific Gravity liquid such as Hydrocarbon,  
 please consult with the manufacturer.

Work No. | **Standard** | Dwg No. | **MP222-140-K32-52-0**

APP'D

CH'D  
 M.Murakami

DWN.  
 M.Murakami



**SANWA HYDROTECH CORP.**

承	
品	
計	