



## PERFORMANCE CURVE

### MAGNET DRIVE CENTRIFUGAL PUMP

Item No.: \_\_\_\_\_  
 Job No.: \_\_\_\_\_  
 \_\_\_\_\_

- **Pump Model** MP420-110-6\*022\*K32\*-2  
 Magnet Coupling Type:           K32N            
 Eddy Current Loss:           0.34           kW
- **Pump Specification**  
 Total Head:           13           m  
 Capacity:           13.2           m<sup>3</sup>/hr              220           L/min  
 Speed:           2940           min<sup>-1</sup>  
 Min.Flow:           0.9           m<sup>3</sup>/hr              15           L/min  
 NPSH av/req:           / -           m

- **Liquid**  
 Name:           -            
 Specific Gravity:           1            
 Viscosity:           1           mPa·s

- **Motor**  
 Power:           2.2 / 4.0           kW

Remark: Recommended Selection Range; 15~220L/min  
 For low Specific Gravity liquid such as Hydrocarbon,  
 please consult with the manufacturer.

|                    |            |            |                    |
|--------------------|------------|------------|--------------------|
| Work No.           | Standard   | Dwg No.    | MP420-110-K32-52-0 |
| APP'D              | CH'D       | DWN.       |                    |
| <i>A. Miyahara</i> | M.Murakami | M.Murakami |                    |

**SANWA HYDROTECH CORP.**

|   |
|---|
| 承 |
| 品 |
| 計 |