



## PERFORMANCE CURVE

### MAGNET DRIVE CENTRIFUGAL PUMP

Item No.: \_\_\_\_\_

Job No.: \_\_\_\_\_

- **Pump Model** MP421-135-6\*015\*K20\*-2  
 Magnet Coupling Type:           K20N            
 Eddy Current Loss:           0.19           kW

- **Pump Specification**  
 Total Head:           20           m  
 Capacity:           13.5           m<sup>3</sup>/hr              225           L/min  
 Speed:           2940           min<sup>-1</sup>  
 Min.Flow:           1.5           m<sup>3</sup>/hr              25           L/min  
 NPSH av/req:           / 2.0           m

- **Liquid**  
 Name:           -            
 Specific Gravity:           1            
 Viscosity:           1           mPa·s

- **Motor**  
 Power:           1.5           kW

Remark: Recommended Selection Range; 25~225L/min  
 For low Specific Gravity liquid such as Hydrocarbon,  
 please consult with the manufacturer.

Work No. | **Standard** | Dwg No. | **MP421-135-K20-52-0**

APP'D <i>A. Nishihata</i>	CH'D M. Murakami	DWN. M. Murakami
------------------------------	---------------------	---------------------



SANWA HYDROTECH CORP.

承
品
計