



## PERFORMANCE CURVE

### MAGNET DRIVE CENTRIFUGAL PUMP

Item No.: \_\_\_\_\_

Job No.: \_\_\_\_\_

: \_\_\_\_\_

- **Pump Model** MP4220LF-200-6\*037\*V25\*-2  
 Magnet Coupling Type:         V25N          
 Eddy Current Loss:     0.61     kW

- **Pump Specification**  
 Total Head:     36     m  
 Capacity:     9.6     m<sup>3</sup>/hr      160   L/min  
 Speed:   2940   min<sup>-1</sup>  
 Min.Flow:     1.5     m<sup>3</sup>/hr        25     L/min  
 NPSH av/req:     /       1.9   m

- **Liquid**  
 Name:         -          
 Specific Gravity:     1      
 Viscosity:     1     mPa·s

- **Motor**  
 Power:     4.0     kW

Remark: Recommended Selection Range; 25~160L/min  
 For low Specific Gravity liquid such as Hydrocarbon,  
 please consult with the manufacturer.

Work No. | **Standard** | Dwg No. | **MP4220LF-200-V25-52-0**

APP'D <i>A. Miyahara</i>	CH'D M.Murakami	DWN. M.Murakami
-----------------------------	--------------------	--------------------

**SANWA HYDROTECH CORP.**

承
品
計