

# PERFORMANCE CURVE

## MAGNET DRIVE CENTRIFUGAL PUMP

Item No.: \_\_\_\_\_

Job No.: \_\_\_\_\_

: \_\_\_\_\_

- **Pump Model** MP4220LF-200-6\*075\*V40\*-2  
Magnet Coupling Type: V40N  
Eddy Current Loss: 1. kW

- **Pump Specification**

Total Head: 36 m  
Capacity: 9.9 m<sup>3</sup>/hr    165 L/min  
Speed: 2940 min<sup>-1</sup>  
Min.Flow: 1.5 m<sup>3</sup>/hr    25 L/min  
NPSH av/req: / 1.9 m

- **Liquid**

Name: -  
Specific Gravity: 1  
Viscosity: 1 mPa·s

- **Motor**

Power: 5.5 / 7.5 kW

Remark: Recommended Selection Range; 25~165L/min  
For low Specific Gravity liquid such as Hydrocarbon,  
please consult with the manufacturer.

Work No. | **Standard** | Dwg No. | **MP4220LF-200-V40-52-0**

APP'D

*A. Miyahara*

CH'D

M.Murakami

DWN.

M.Murakami



**SANWA HYDROTECH CORP.**

承	
品	
計	

————— : Recommended Selection Range

