



## PERFORMANCE CURVE

### MAGNET DRIVE CENTRIFUGAL PUMP

Item No.: \_\_\_\_\_

Job No.: \_\_\_\_\_

: \_\_\_\_\_

- **Pump Model** MP5225LF-250-6\*075\*V40\*-2  
 Magnet Coupling Type:       V40N        
 Eddy Current Loss:       1.       kW

- **Pump Specification**  
 Total Head:       59       m  
 Capacity:       15       m<sup>3</sup>/hr          250       L/min  
 Speed:       2970       min<sup>-1</sup>  
 Min.Flow:       1.8       m<sup>3</sup>/hr          30       L/min  
 NPSH av/req:       / -       m

- **Liquid**  
 Name:       -        
 Specific Gravity:       1        
 Viscosity:       1       mPa·s

- **Motor**  
 Power:       5.5 / 7.5       kW

Remark: Recommended Selection Range; 30~250L/min  
 For low Specific Gravity liquid such as Hydrocarbon,  
 please consult with the manufacturer.

Work No. | **Standard** | Dwg No. | **MP5225LF-250-V40-52-0**

APP'D <i>A. Miyahara</i>	CH'D M.Murakami	DWN. M.Murakami
-----------------------------	--------------------	--------------------



SANWA HYDROTECH CORP.

承
品
計