



## PERFORMANCE CURVE

### MAGNET DRIVE CENTRIFUGAL PUMP

Item No.: \_\_\_\_\_

Job No.: \_\_\_\_\_

: \_\_\_\_\_

- **Pump Model** MP5225LF-250-6\*150\*V65\*-2  
 Magnet Coupling Type:         V65N          
 Eddy Current Loss:     1.27     kW

- **Pump Specification**  
 Total Head:     59     m  
 Capacity:     15     m<sup>3</sup>/hr        250     L/min  
 Speed:     2970     min<sup>-1</sup>  
 Min.Flow:     1.8     m<sup>3</sup>/hr        30     L/min  
 NPSH av/req:     / -     m

- **Liquid**  
 Name:     -      
 Specific Gravity:     1      
 Viscosity:     1     mPa·s

- **Motor**  
 Power:     11 / 15     kW

Remark: Recommended Selection Range; 30~250L/min  
 For low Specific Gravity liquid such as Hydrocarbon,  
 please consult with the manufacturer.

Work No. | **Standard** | Dwg No. | **MP5225LF-250-V65-52-0**

APP'D <i>A. Miyahara</i>	CH'D M.Murakami	DWN. M.Murakami
-----------------------------	--------------------	--------------------

**SANWA HYDROTECH CORP.**

承
品
計