



## PERFORMANCE CURVE

### MAGNET DRIVE CENTRIFUGAL PUMP

Item No.: \_\_\_\_\_  
 Job No.: \_\_\_\_\_  
 \_\_\_\_\_

● **Pump Model** MP5430-160-6\*110\*V65\*-2  
 Magnet Coupling Type:         V65N          
 Eddy Current Loss:     1.27     kW

● **Pump Specification**  
 Total Head:     21     m  
 Capacity:     24.3     m<sup>3</sup>/hr        405     L/min  
 Speed:     2970     min<sup>-1</sup>  
 Min.Flow:     2.4     m<sup>3</sup>/hr        40     L/min  
 NPSH av/req:     / 2.5     m

● **Liquid**  
 Name:         -          
 Specific Gravity:     1      
 Viscosity:     1     mPa·s

● **Motor**  
 Power:     11 / 15     kW

Remark: Recommended Selection Range; 40~405L/min  
 For low Specific Gravity liquid such as Hydrocarbon,  
 please consult with the manufacturer.

Work No.	Standard	Dwg No.	MP5430-160-V65-52-0
APP'D	CH'D	DWN.	
<i>A. Miyahara</i>	M.Murakami	M.Murakami	

**SANWA HYDROTECH CORP.**

承
品
計