



## PERFORMANCE CURVE

### MAGNET DRIVE CENTRIFUGAL PUMP

Item No.: \_\_\_\_\_

Job No.: \_\_\_\_\_

● **Pump Model** MP5430-180-6\*110\*V65\*-2  
 Magnet Coupling Type:         V65N          
 Eddy Current Loss:     1.27     kW

● **Pump Specification**  
 Total Head:     30     m  
 Capacity:     27.3     m<sup>3</sup>/hr        455     L/min  
 Speed:     2970     min<sup>-1</sup>  
 Min.Flow:     2.4     m<sup>3</sup>/hr        40     L/min  
 NPSH av/req:     / 2.5     m

● **Liquid**  
 Name:         -          
 Specific Gravity:     1      
 Viscosity:     1     mPa·s

● **Motor**  
 Power:     11 / 15     kW

Remark: Recommended Selection Range; 40~455L/min  
 For low Specific Gravity liquid such as Hydrocarbon,  
 please consult with the manufacturer.

Work No. | **Standard** | Dwg No. | **MP5430-180-V65-52-0**

|                              |                     |                     |
|------------------------------|---------------------|---------------------|
| APP'D<br><i>A. Nishihata</i> | CH'D<br>M. Murakami | DWN.<br>M. Murakami |
|------------------------------|---------------------|---------------------|



SANWA HYDROTECH CORP.

|   |
|---|
| 承 |
| 品 |
| 計 |