



## PERFORMANCE CURVE

### MAGNET DRIVE CENTRIFUGAL PUMP

Item No.: \_\_\_\_\_  
 Job No.: \_\_\_\_\_  
 \_\_\_\_\_

● **Pump Model** MP5430-190-6\*075\*V40\*-2  
 Magnet Coupling Type:       V40N        
 Eddy Current Loss:       1.       kW

● **Pump Specification**  
 Total Head:       34       m  
 Capacity:       28.8       m<sup>3</sup>/hr          480       L/min  
 Speed:       2970       min<sup>-1</sup>  
 Min.Flow:       2.4       m<sup>3</sup>/hr          40       L/min  
 NPSH av/req:       / 2.5       m

● **Liquid**  
 Name:       -        
 Specific Gravity:       1        
 Viscosity:       1       mPa·s

● **Motor**  
 Power:       5.5 / 7.5       kW

Remark: Recommended Selection Range; 40~480L/min  
 For low Specific Gravity liquid such as Hydrocarbon,  
 please consult with the manufacturer.

Work No.	Standard	Dwg No.	MP5430-190-V40-52-0
APP'D	CH'D	DWN.	
<i>A. Nishihata</i>	M. Murakami	M. Murakami	

**SANWA HYDROTECH CORP.**

承
品
計