

# PERFORMANCE CURVE

## MAGNET DRIVE CENTRIFUGAL PUMP

Item No.: \_\_\_\_\_

Job No.: \_\_\_\_\_

: \_\_\_\_\_

- **Pump Model** MP5430-190-6\*110\*V65\*-2  
Magnet Coupling Type: V65N  
Eddy Current Loss: 1.27 kW

- **Pump Specification**

Total Head: 34 m  
Capacity: 28.8 m<sup>3</sup>/hr    480 L/min  
Speed: 2970 min<sup>-1</sup>  
Min.Flow: 2.4 m<sup>3</sup>/hr    40 L/min  
NPSH av/req: / 2.5 m

- **Liquid**

Name: -  
Specific Gravity: 1  
Viscosity: 1 mPa·s

- **Motor**

Power: 11 / 15 kW

Remark: Recommended Selection Range; 40~480L/min  
For low Specific Gravity liquid such as Hydrocarbon,  
please consult with the manufacturer.

Work No. | **Standard** | Dwg No. | **MP5430-190-V65-52-0**

APP'D

*A. Miyahara*

CH'D

M.Murakami

DWN.

M.Murakami



**SANWA HYDROTECH CORP.**

承	
品	
計	

— : Recommended Selection Range

