



## PERFORMANCE CURVE

### MAGNET DRIVE CENTRIFUGAL PUMP

Item No.: \_\_\_\_\_  
 Job No.: \_\_\_\_\_  
 \_\_\_\_\_

● **Pump Model** MP8415-160-6\*037\*V25\*-2  
 Magnet Coupling Type:       V25N        
 Eddy Current Loss:       0.61       kW

● **Pump Specification**  
 Total Head:       24       m  
 Capacity:       39.6       m<sup>3</sup>/hr          660       L/min  
 Speed:       2960       min<sup>-1</sup>  
 Min.Flow:       3       m<sup>3</sup>/hr          50       L/min  
 NPSH av/req:       / 2.0       m

● **Liquid**  
 Name:       -        
 Specific Gravity:       1        
 Viscosity:       1       mPa·s

● **Motor**  
 Power:       4.0       kW

Remark: Recommended Selection Range; 50~660L/min  
 For low Specific Gravity liquid such as Hydrocarbon,  
 please consult with the manufacturer.

Work No.	Standard	Dwg No.	MP8415-160-V25-52-0
APP'D	CH'D	DWN.	
<i>A. Miyahara</i>	M.Murakami	M.Murakami	

**SANWA HYDROTECH CORP.**

承
品
計