



## PERFORMANCE CURVE

### MAGNET DRIVE CENTRIFUGAL PUMP

Item No.: \_\_\_\_\_  
 Job No.: \_\_\_\_\_  
 \_\_\_\_\_

● **Pump Model** MP8515-160-6\*075\*V40\*-2  
 Magnet Coupling Type:       V40N        
 Eddy Current Loss:       1.       kW

● **Pump Specification**  
 Total Head:       23       m  
 Capacity:       51.6       m<sup>3</sup>/hr          860       L/min  
 Speed:       2960       min<sup>-1</sup>  
 Min.Flow:       4.8       m<sup>3</sup>/hr          80       L/min  
 NPSH av/req:       / 2.1       m

● **Liquid**  
 Name:       -        
 Specific Gravity:       1        
 Viscosity:       1       mPa·s

● **Motor**  
 Power:       5.5 / 7.5       kW

Remark: Recommended Selection Range; 80~860L/min  
 For low Specific Gravity liquid such as Hydrocarbon,  
 please consult with the manufacturer.

Work No.	Standard	Dwg No.	MP8515-160-V40-52-0
APP'D	CH'D	DWN.	
<i>A. Mizuhata</i>	M.Murakami	M.Murakami	

**SANWA HYDROTECH CORP.**

承
品
計